Applicant: Coach Wei, et al

U.S.S.N.:

10/017,183

Filing Date: 12/7/2001

EMC Docket No.: EMC-06-235(Pro)Ord1

In the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the

Application.

Listing of Claims:

1. (Currently amended) A method for delivering an application over a network in which

the business logic of the application is running on a backend server, the method comprising the

steps of:

having the application invoke a Graphic User Interface (GUI) Application Programming

<u>Interface (API)</u> to present the application's user interface;

initiating a thread for replacing the GUI API with a re-implemented network aware GUI

API running on a backend server [[which]] that translates the application's presentation layer

information into pre-determined format based messages [[which]] that describe a Graphical User

Interface, event processing registries, and other related information corresponding to:

the presentation layer of the application in high level, object level, messages;

sending such messages to the client device via [[a]] the network;

processing the messages and rendering a user interface by a client-side program, which

delivers a user experience for that device according to the capability of the specific client device;

rendering the user interface on the client device;

transmitting a plurality of necessary user input and a plurality of client-side events back

to the server by the client side program via a predetermined protocol;

-3-

Applicant: Coach Wei, et al

U.S.S.N.:

10/017,183

Filing Date: 12/7/2001

EMC Docket No.: EMC-06-235(Pro)Ord1

processing the user input and client-side events on the backend server, translating the events and inputs as if they were locally generated, and sending such translated events and inputs to the application for processing;

encoding and routing output of the application to the client device using the predetermined messaging format; and,

further processing the output by the client-side program to refresh the Graphical User Interface [[thereat]] thread and extinguishing said thread upon completion;

wherein use of the re-implemented network aware API enables the application to be developed once and deployed multiple times.

- 2. (Currently amended) The method of Claim 1, wherein the GUI API and the event processing API are represented as classes within Java Foundation Classes.
- 3. (Currently amended) The method of Claim 1, wherein the client-side program is a computer program based on an Operating System's API [[, such as Windows API, or X Windows API]].
- 4. (Currently amended) The method of Claim 1, wherein the client-side program is a wireless device program written using the device's Operating System's API [[, such as Palm API and Windows CE AP[]].

Applicant: Coach Wei, et al U.S.S.N.: 10/017,183

Filing Date: 12/7/2001

EMC Docket No.: EMC-06-235(Pro)Ord1

5. (Currently amended) The method of Claim 1, wherein the client-side program is a [[Java]] program written using a Java API.

6. (Currently amended) The method of Claim 5, wherein the JAVA API is selected from the groups consisting of: Abstract Windows Toolkit (AWT), Personal Java, Java 2 Micro Edition based GUI API or Java Swing.

7. (Currently amended) The method of Claim 1, wherein the predetermined protocol is Hyper Text Transfer Protocol (HTTP).

- 8. (Currently amended) The method of Claim 1, wherein the predetermined protocol is Hyper Text Transfer Protocol over Secure Socket Layer (HTTPS).
- 9. (Currently amended) The method of Claim 1, wherein predetermined protocol is Wireless Application Protocol (WAP).
- 10. (Original) The method of Claim 1, wherein predetermined protocol is proprietary.
- 11. (Currently amended) The method of Claim 1, wherein the predetermined messaging format is based on Extended Markup Language (XML).

Applicant: Coach Wei, et al U.S.S.N.: 10/017,183 Filing Date: 12/7/2001

EMC Docket No.: EMC-06-235(Pro)Ord1

12. (Previously presented) The method of Claim 1, wherein the predetermined messaging format is proprietary.

- 13. (Original) The method of Claim 1, wherein the network is the Internet.
- 14. (Original) The method of Claim 1, wherein the network is a local area network.
- 15. (Original) The method of Claim 8, wherein the local area network is a bandwidth-limited slow speed network.
- 16. (Original) The method of Claim 1, wherein the network includes a wireless network.
- 17. (Currently amended) The method of Claim 11, wherein the client device is selected from the group consisting of workstations, desktops, laptops, <u>Personal Digital Assistants (PDAs)</u>, and wireless devices and other edge devices.
- 18. (Original) The method of Claim 1, wherein the server and the client device are combined into one entity.
- 19. (Cancelled)
- 20. (Cancelled)

Applicant: Coach Wei, et al

U.S.S.N.:

10/017,183

Filing Date: 12/7/2001

EMC Docket No.: EMC-06-235(Pro)Ord1

21. (Cancelled)

22. (Currently amended) A system for distributing an application including at least a server, at

least a client device, and a communication means, the system comprising:

a presentation layer of the application written using a server-side API based network

programming model;

a business logic layer of the application and a data layer of the application both of which

are written with the server-side API and running on the server; and where

the server-side API having a supporting infrastructure <u>initiating a thread</u> that:

sends the application's user interface information to a client device for

presentation,

handles communications problems,

renders the application's user interface, and

dispatches necessary user input events back to the server for processing; and

extinguishes said thread after said processing is completed,

wherein use of the system enables the application to be developed once and deployed

multiple times.

23. (Currently amended) An apparatus for distributing an application over a network where the

apparatus includes:

a server;

-7-

Applicant: Coach Wei, et al 10/017,183

U.S.S.N.:

Filing Date: 12/7/2001

EMC Docket No.: EMC-06-235(Pro)Ord1

a client device;

a network communication means;

a re-implemented, network based API module that is used to transparently replace the

API on which the application was developed;

a first means for running an application of the plurality of applications where a business

logic of the application runs on the server;

a second means for initiating a thread for replacing the API of each of the plurality of

applications with the network based API so that each of the applications' logic runs on the

server;

a third means for using the network based API to create a display for an application on

the client device;

a fourth means for transferring the user interactions on the client device to the server,

calculating the appropriate response to the input, and transmitting the appropriate response to the

client machine;

a fifth means for updating the display of the application on the client device based on the

responses from the server; and

a sixth means for extinguishing said thread after processing has been completed,

wherein use of the re-implemented network aware API enables the application to be

developed once and deployed multiple times.

24. (Previously presented) The method of Claim 1 wherein the application code is not modified

when distributing the application and the application code is not distributed to the client device.

-8-

Applicant: Coach Wei, et al U.S.S.N.: 10/017,183

Filing Date: 12/7/2001 EMC Docket No.: EMC-06-235(Pro)Ord1

25. (Previously presented) The method of Claim 1 used to distribute a plurality of pre-existing applications.